

IXWL-35

Intel® Whiskey Lake U/Comet Lake U based Embedded Industrial PC



Features

- CPU: Intel® Whiskey Lake U/Comet Lake U processor
- Memory: Dual Channel SO-DIMM DDR4 up to 64 GB
- Display: Intel® UHD Graphics via HDMI, DP, VGA optional
- Ethernet: 10/100/1000Mbps
- Storage: SATA3.0, 1x M.2 for 2242 SSD/4G
- Expansion: M.2 for WiFi
- Power: 12V/19V DC input, Phoenix input optional





Technical Specifications

Processor	Comet Lake U	i3-10110U	i5-10210U	
	Base Frequency	2.1GHz	1.6 GHz	
	Max Turbo Frequency	4.1GHz	4.2 GHz	
	Cache	4MB	6MB	
	Whiskey Lake U	Pentium 5405U	Celeron 4205U	i3-8145U
	Base Frequency	2.3 GHz	1.8 GHz	2.1 GHz
	Max Turbo Frequency	/	/	3.9 GHz
	Cache	2MB	2MB	4MB
	TDP	15W		
	BIOS	AMI UEFI BIOS		
Memory	Type	Dual Channel SO-DIMM DDR4		
	Max capacity	64GB		
Display	GPU	Integrated Intel® UHD Graphics based on CPU		
	Display via	HDMI+DP+VGA optional		
Ethernet	Speed	10/100/1000Mbps		
	Controller	1x Intel® i210 + 1x Intel® i219		
	Interface	2x RJ45		
Audio	Wake on LAN	Yes		
	Audio codec	Realtek HD		
Hardware	Interface	1xCTIA 2-in-1 Audio Jack		
		System temperature, Onboard voltage, Watchdog, Auto power on		
Storage	M.2	1x M.2 for 2242 SSD/4G		
	SATA	1x SATA3.0		
Expansion	M.2	1x M.2 for Wi-Fi		
Other I/O	COM	Default: 2xRS485 +4xRS232		
		Optional: 1xRS485+VGA +4xRS232		
	USB2.0	4		
	USB3.2	4		
Dimension	Size	165mm x 125mm x 65mm		
Power	Standard input	12V/19V DC-IN		
	Phoenix input	16-30V Phoenix input optional		
	Peripheral Input	For Fan and SATA		
	LED Indicator	Power indicator		
Temperature	Operating Temp.	-20°C to 60°C		
	Storage Temp.	-40°C to 80°C		
Cooling		Passive		
Operating System		Win7/8/10 32/64bit, Linux 32/64 bit		

Dimensi

Ma'ā g